THE USE OF WALSH FUNCTIONS FOR MULTIPLEXING SIGNALS

by

I.A. Davidson

Research and Development Laboratories
Northern Electric Company Ltd.
Ottawa, Canada

Introduction

Walsh functions can be used as carriers of information in a multiplex system such as a system for the simultaneous transmission of a number of telephone signal on a common cable. For this application the orthogonal properties of Walsh functions can be used to maintain the identity of the signals in each channel.

Walsh Functions

Walsh functions are a set of binary functions that are periodic and orthogonal. Examples of the first 15 functions are shown in Figure 1. These functions have been described by Walsh[1], Bell[2] and Harmuth[3] where the set of functions have been sub-divided into two groups called Sal and Cal functions, which correspond to the circular functions Sine and Cosine. However the complete set can be defined by a single function that includes the Sal and Cal functions.

The most compact form of the function is given in Iversons[4] notation as

$$\neq /(A \wedge B) \tag{1}$$

where A and B are integers in binary form, both having the same number of binary bits

$\wedge$ indicates a logical AND function between corresponding bits

$\neq /$ indicates an exclusive OR compression, i.e. adjacent bits are combined by an exclusive OR operation.

This compact expression can be written as

$$(a_n \wedge b_n) \oplus (a_{n-1} \wedge b_{n-1}) \oplus (a_2 \wedge b_2) \oplus (a_1 \wedge b_1) \tag{2}$$

where $a_n \ldots a_1$ and $b_2 \ldots b_1$ are the binary digits of A and B and $\oplus$ represents an exclusive OR function.

This expression gives a logical combination of two binary numbers A and B. If A is an integer k and B is a function of time θ, it is possible to define a Walsh function by the expression

$$WALSH(k,\theta) = \neq /(k \wedge - \alpha\theta) \tag{3}$$

where α is a factor chosen to make the function periodic in the range $0 < \theta < 1$. The minus sign is chosen before θ to ensure that the functions are identical to the Sal and Cal functions given above.

The above definition can be restated by the following equation, which indicates the logic system that can be used to generate them.

$$WALSH(k,\theta) = (a_1 s(\theta)) \oplus (a_2 s(2\theta)) \oplus (a_3 s(4\theta)) \oplus \ldots$$
$$\ldots \oplus (a_{n-1} s(2^{n-2}\theta)) \oplus (a_n s(2^{n-1}\theta)) \tag{4}$$

where k is an integer whose binary digits are $a_1, a_2 \ldots a_n$

i.e. $k = 2^{n-1}a_n + 2^{n-2}a_{n-1} + \ldots + 2a_2 + a_1$

and $s(x)$ is a square wave function of x

i.e. $s(x) = 0$ for $0 \leq x < \frac{1}{2}$, $1 \leq x < 1\frac{1}{2}$, etc.

$\quad = 1$ for $\frac{1}{2} \leq x < 1$, $1\frac{1}{2} \leq x < 2$, etc.

and $\oplus$ is the exclusive OR function.

i.e. $a \oplus b = 0$ if $a = b$ and $a \oplus b = 1$ if $a \neq b$

The functions defined by this equation are periodic, typified by the range $0 < \theta < 1$. All the functions are synchronized, such that at time $\theta = 0$ all the functions have zero value.

This definition has another important property. As it can be seen from that the first definition it is symmetrical with respect to A and B. The Walsh function is therefore symmetrical between the integer k and the time θ. By interchanging these two variables the same system will give the values of all the orders of Walsh functions at a given time. This property has been described by Shanks[5] and is useful in a system for generating fast Walsh transforms of a function.

Generation of Walsh Functions

Walsh functions can be generated by the system shown by the block diagram in Figure 2. The operation of this can be related to Equation (2): A square wave function on the left is divided by 2 at each stage, enabling the functions $s(\theta)$, $s(2\theta)$ etc. to be generated. These are selected by the switches a_1, a_2 etc. corresponding to the binary bits of the integer k. The signals are combined by the series of exclusive - OR gates. The complete Walsh waveform appears at the right hand side of the system.

Each section of this system can be implemented by the arrangement of logic circuits shown in Figure 3. The JK flip-flop divides

the incoming square wave. The switch and two exclusive-OR functions are combined in one group of NAND gates. It can be seen that the system can be extended to any order of Walsh function by the addition of further identical sections.

The maximum speed of the system is determined by the propagation time of pulses through the system, and the time difference between the propagation through the chain of Exclusive OR and through the divide by two circuits. Using TTL integrated circuits as the basic logic elements an eight stage system has been constructed and driven at a frequency of 1 MHz. Under these conditions the output can be changed from WALSH (1,θ) up to WALSH (255,θ), the lowest frequency being 7.8 KHz (WALSH (1,θ) and WALSH (3,θ)) and the highest frequency being 1 MHz (WALSH (128, θ). Figure 4 is an oscilloscope trace of a typical waveform as generated by the system.

Multiplexing of Signals

As the Walsh functions are all orthogonal it is possible to use them as carriers of information. If a signal is amplitude modulated by a given Walsh function, multiplying it by an identical Walsh function will extract the modulation. Multiplying it by any other Walsh function will result in a zero signal.

The orthogonality of the signals is only established if the two Walsh waveforms are synchronized and are in phase. One method of achieving this is to transmit a synchronizing square wave, the leading edge of this (or the positive transition) being used to synchronize the Walsh waveform generator at the receiving end. The amplitude of the signal is carried by the trailing edge (or the negative transition) of the square wave. In this way the Walsh function generator can be triggered to its next value well before the transition containing the signal is received.

At the end of each cycle the synchronizing signal is interrupted for approximately 2 μs as shown in Figure 5. A reset pulse can be extracted from this for initializing the Walsh generator. This will only be necessary at the beginning of operation, in the event of interruption or if synchronization is lost due to noise signals. It can be seen that all the Walsh functions are zero immediately following the synchronizing pulse, and therefore no signal information is carried at that time. This will enable all the waveforms to be correctly phased by the time the first information signal arrives.

The modulation process consists of generating one cycle similar to the synchronizing waveform, but having an amplitude equal to that of the signal whenever the Walsh function is 'one', and having zero amplitude if the Walsh function is 'zero'. Examples of modulated signals are shown in Figure 6. In the demodulation process the amplitude of the negative transition of the waveform is extracted and either added or subtracted from the output depending on whether the Walsh function is 'one' or 'zero'.

System Performance

Study of the model of the system gives the performance to be expected, and two possible sources of cross modulation become evident. The first arises from unbalance in the receiving circuit, and the second from loss of phase synchronization.

The rejection of signals carried by other channel Walsh functions depends on the cancellation of the signal after it has been 'multiplied' by a different Walsh function. This involves the adding together of a number of signals, with suitable sign changes, to give a zero result. This requires careful circuit design for satisfactory signal performance to be achieved under working conditions.

A small shift of phase synchronization would superimpose the information in a given time slot on the next time slot. Poor repeater response or lack of phase equalization would give a similar result. The effect of this has been simulated by a computer program. It was shown that the magnitude of the cross modulation was small except in the case of certain pairs of channels. These channel pairs have the same order of Walsh functions except for the first binary bit, i.e. channels 251 and 123. However, if these pairs of channels are chosen in the same way as cable pairs in a multi-wire cable, and balanced signals placed on them, the effect of cross modulation becomes less important. This has the added advantage that signals do not amplitude modulate the carrier, thereby reducing the cross modulation due to non-linear components in the system.

Conclusion

Parts of an experimental setup have been built in order to test the critical parts of it. Furthermore study of the model should give its expected characteristics, including such secondary parameters as the effects of phase delay and linearity of repeater amplifiers, signal clipping, channel noise, etc. However, the final check must come from fully engineered systems with its performance evaluated under operating conditions.

References

1. Walsh, J.L., "A Closed Set of Normal Orthogonal Functions", American Journal of Mathematics, Vol. 55, p. 5-24, 1923.

2. Bell, D.A., "Walsh Functions and Hadamand Matrices", Electronic Letters, Vol. 2, No. 9, p. 340, September 1966.

3. Marmuth, H.F., "A Generalized Concept of Frequency and Some Applications", IEEE Transactions on Information Theory Vol. IT-14, p. 375-382, May 1968.

4. Iverson, K.E., "A Programming Language", John Wiley & Sons, 1966.

5. Shanks, J.L., "Computation of the Fast Walsh Fourier Transform", IEEE Transactions on Computers, May 1969.

FIGURE 1

Labels (left column, top to bottom):
WALSH (1,0) (SUB (1,0))
WALSH (2,0) (CAL (2,0))
WALSH (3,0) (CAL (1,0))
WALSH (4,0) (CAL (4,0))
WALSH (5,0) (SAL (3,0))
WALSH (6,0) (SAL (2,0))
WALSH (7,0) (CAL (3,0))
WALSH (8,0) (SAL (8,0))
WALSH (9,0) (CAL (7,0))
WALSH (10,0) (SAL (6,0))
WALSH (11,0) (SAL (7,0))
WALSH (12,0) (SAL (4,0))
WALSH (13,0) (CAL (5,0))
WALSH (14,0) (CAL (6,0))
WALSH (15,0) (SAL (5,0))

FIGURE 2

SQUARE WAVE INPUT
WALSH OUTPUT

BINARY BIT INPUT
SIGNAL INPUT
SIGNAL OUTPUT
OUTPUT
SQUARE WAVE INPUT
CLOCK   JK
SQUARE WAVE OUTPUT

FIGURE 3

Figure 4   Walsh Waveform

Figure 5   a) Walsh Waveform
b) Synchronizing Waveform


WALSH (5,0)
SMALL SIGNAL MODULATED
WALSH (13,0)
LARGE SIGNAL MODULATED
SYNC SIGNAL
COMPOSITE WAVEFORM

FIGURE 6

25